

SLIM S HVLP

- **Needle-springs:** stainless steel
 - **Sealing gaskets:** PTFE (teflon) self-lubricating and self adjusting
 - **Nozzle:** AISI 303 stainless steel
- NEW**
- **Body:** chromium plated polished aluminium
 - **Air cap:** anodized aluminium
 - **Ø nozzle:** 1,3 - 1,5 - 1,7 - 1,9 - 2,2

Air flow inlet regulator with manometer


REF.*				
10060**	Hostaform C® 680 cc.	880 gr.	2 Bar	200 lt./min.



SLIM S HVLP

- **Needle-springs:** stainless steel
 - **Sealing gaskets:** PTFE (teflon) self-lubricating and self adjusting
 - **Nozzle:** AISI 303 stainless steel
- NEW**
- **Body:** chromium plated polished aluminium
 - **Air cap:** anodized aluminium
 - **Ø nozzle:** 1,3 - 1,5 - 1,7 - 1,9 - 2,2

Air flow inlet regulator with manometer

REF.*				
10061**	aluminium 750 cc.	820 gr.	2 Bar	200 lt./min.



SLIM I HVLP

- **Needle-springs:** stainless steel
 - **Sealing gaskets:** PTFE (teflon) self-lubricating and self adjusting
 - **Nozzle:** AISI 303 stainless steel
- NEW**
- **Body:** chromium plated polished aluminium
 - **Air cap:** anodized aluminium
 - **Ø nozzle:** 1,7 - 1,9 - 2,2

Air flow inlet regulator with manometer

REF.*				
10070**	aluminium 1000 cc.	1010 gr.	2 Bar	200 lt./min.



SLIM SP HVLP

- **Needle-springs:** stainless steel
 - **Sealing gaskets:** PTFE (teflon) self-lubricating and self adjusting
 - **Use:** through pressurized containers or low pressure pumps
- NEW**
- **Body:** chromium plated polished aluminium
 - **Air cap:** anodized aluminium
 - **Nozzle:** AISI 303 stainless steel
 - **Ø nozzle:** 1,0 - 1,3 - 1,5 - 1,7

Air flow inlet regulator with manometer




REF.*				
10071**	air inlet M1/4"	660 gr.	2 Bar	200 lt./min.



*Add nozzle Ø to REF.

SLIM S

- **Needle-springs:** stainless steel
 - **Sealing gaskets:** PTFE (teflon) self-lubrificating and self adjusting
 - **Nozzle:** AISI 303 stainless steel
- NEW**
- **Body:** chromium plated polished aluminium
 - **Air cap:** anodized aluminium
 - **Ø nozzle:** 1,3 - 1,5 - 1,7 - 1,9 - 2,2 - 2,5

REF.*				
10062**	Hostaform C® 680 cc	730 gr.	2,5 - 3 Bar	240/280 lt./min.
10063**	aluminium 750 cc	670 gr.	2,5 - 3 Bar	240/280 lt./min.



SLIM I

- **Needle-springs:** stainless steel
 - **Sealing gaskets:** PTFE (teflon) self-lubrificating and self adjusting
 - **Nozzle:** AISI 303 stainless steel
- NEW**
- **Body:** chromium plated polished aluminium
 - **Air cap:** anodized aluminium
 - **Ø nozzle:** 1,3 - 1,5 - 1,7 - 1,9 - 2,2 - 2,5

REF.*				
10072**	aluminium 1000 cc	860 gr.	2,5 - 3 Bar	240/280 lt./min.



14
15

SLIM SP

- **Needle-springs:** stainless steel
 - **Sealing gaskets:** PTFE (teflon) self-lubrificating and self adjusting
 - **Use:** through pressurized containers or low pressure pumps
- NEW**
- **Body:** chromium plated polished aluminium
 - **Air cap:** anodized aluminium
 - **Nozzle:** AISI 303 stainless steel
 - **Ø nozzle:** 1,0 - 1,3 - 1,5 - 1,7 - 1,9

REF.*				
10073**	air inlet M1/4"	510 gr.	2,0 - 2,5 Bar	200/240 lt./min.



NEW SLIM S HD

- **Needle-springs:** stainless steel
 - **Sealing gaskets:** PTFE (teflon) self-lubrificating and self adjusting
- NEW**
- **Body:** chromium plated polished aluminium
 - **Air cap:** anodized aluminium
 - **Nozzle:** AISI 303 stainless steel
 - **Ø nozzle:** 1,5 - 1,9 - 2,2 - 2,5
- **Pressurized gravity cup:** for high density products
 - **Double air flow regulator and pressurized gravity cup with manometer**
 - **Use:** for high density products like Latex, Polyurethans, Gel Coat, Thixotropic of the wood and industrial sector

REF.*				
10064**	air inlet M1/4"	1220 gr.	2,0 - 2,5 Bar	200/240 lt./min.



*Add nozzle Ø to REF.