

G1

- **Body:** nickel-plated sanded brass
- **Needle-nozzle-springs:** stainless steel
- **Cap:** nickel-plated brass
- **Suction cup:** with adjustable pressure
- **Adjustments:** product -fan
- **Cup gasket:** o-ring in NBR
- **Equipped with regulator group of the air inlet and air pressure to the tank.**
- **Ø nozzle:** 1,9 - 2,2 - 2,5

REF.*				AIR
361**	stainless steel 1000 cc	1700 gr.	MAX 3 Bar	370 lt./min.



G1/SP

- **Body:** nickel-plated sanded brass
- **Needle-nozzle-springs:** stainless steel
- **Cap:** nickel-plated brass
- **Adjustments:** product - fan
- **Cup gasket:** o-ring in NBR
- **Ø nozzle:** 1,9 - 2,2 - 2,5

REF.*	SP			AIR
363**	product inlet M1/4"	620 gr.	MAX 3 Bar	370 lt./min.



G1/T

- **Body:** nickel-plated sanded brass
- **Needle-nozzle-springs:** stainless steel
- **Cap:** nickel-plated brass
- **Suction cup:** with adjustable pressure
- **Adjustments:** product
- **Cup gasket:** o-ring in NBR
- **Round spray**
- **Equipped with regulator group of the air inlet flow and air pressure to the tank**
- **Ø nozzle:** 1,9 - 2,2 - 2,5

REF.*				AIR
362**	stainless steel 1000 cc	1670 gr.	MAX 3 Bar	230 lt./min.



G1/T SP

- **Needle-nozzle-springs:** stainless steel
- **Cap:** nickel-plated brass
- **Adjustments:** product
- **Body:** nickel-plated sanded brass
- **Round spray**
- **Ø nozzle:** 1,9 - 2,2 - 2,5

REF.*	SP			AIR
364**	product inlet M1/4"	620 gr.	MAX 3 Bar	230 lt./min.



*Add nozzle Ø to the REF.

RD

- **Body:** nickel-plated sanded brass
- **Adjustments:** product -fan
- **Needle-nozzle-springs:** stainless steel
- **ø nozzle:** 1,7
- **Cap:** nickel-plated brass, swivelling 360° for lateral spraying




REF.*				
36617	nylon 680 cc	1050 gr.	3 - 4 Bar	130 - 200 lt./min



NEW EPD-EPD/L

Spray gun for pressurized high density products without atomising air. Ideal for glue, sealing and lubricant.

- **Body:** nickel-plated sanded brass
- **Adjustments:** product
- **Barrel:** 100 mm with product blocking on the tip, equipped with interchangeable flat spout in metal
- **Barrel (EPD/L):** 150 mm, diam. Int. 4 mm with product blocking at the tip of the barrel on the screwable nozzle

REF.*			
36700 EPD	370 gr.	MAX 3 Bar	30/60 lt./min.
36800 EPD /L	345 gr.		



16
17

NEW MM

- **Body:** varnished aluminium
- **Needle-springs:** brass
- **Nozzle:** nickel-plated brass
- **Use:** application of plastic wall paint
- **Cap:** nickel-plated brass
- **Adjustments:** product
- **ø nozzle:** 4,5 - 6,0 - 8,0

REF.*				
62007	nylon 4,75 lt	1360 gr.	3,4 - 4,8 Bar	120 lt./min.



*Add nozzle ø to the REF.