

X 400 AUT

Professional automatic quick coupling for compressed air equipped with a blocking system with 6 stainless steel balls. Japanese Standard. CEMENTED STEEL front and nut gurantees long lasting and efficiency especially for heavy use such as pneumatic tools. Plugs in CEMENTED STEEL.

MALE

REF.	THREAD		
10101	1/4"U	10	
10102	3/8"U	10	



FEMALE

REF.	THREAD		
10111	1/4"U	10	
10112	3/8"U	10	



WITH REST

REF.	ø INT.		
10122	8	10	
10123	10	10	



MALE PLUGS

REF.	THREAD		
11470	1/4"U	10	
11471	3/8"U	10	



FEMALE PLUGS

REF.	THREAD		
11480	1/4"U	10	
11481	3/8"U	10	



X 300 U


Automatic couplings for compressed air compatible with the most common plugs.

With high delivery and long life, the product has two innovative features:

- Mechanical locking with 6 steel radial ball.
- Pneumatic sealing with variable compression desmodronic gaskets


PATENTED

MALE

REF.	THREAD		
10201U	1/4"	25	
10202U	3/8"	25	
10203U	1/2"	25	




FEMALE

REF.	THREAD		
10211U	1/4"	25	
10212U	3/8"	25	
10213U	1/2"	25	




54
55

WITH REST

REF.	ø INT.		
10221U	6	25	
10222U	8	25	
10223U	10	25	




FOR RUBBER HOSE

REF.	ø INT. ø EXT.		
10231U	6/14	25	
10234U	8/14	25	
10232U	8/17	25	
10233U	10/19	25	



FOR NYLON HOSE WITH SPRING

REF.	THREAD		
10241U	6x8	25	
10242U	8x10	25	
10243U	6x10	25	
10244U	8x12	25	
10246U	10x12	25	




GLOBAL U

Automatic coupling for compressed air, compatible with the most common plugs.

Created from the positive results of the X 300 U, the GLOBAL U has the same features and functions.


The push rod and ring in Zamak allow the product to reach an interesting cost/price ratio.

MALE

REF.	THREAD		
10301U	1/4"	25	
10302U	3/8"	25	
10303U	1/2"	25	




FEMALE

REF.	THREAD		
10311U	1/4"	25	
10312U	3/8"	25	
10313U	1/2"	25	




WITH REST

REF.	ø INT.		
10321U	6	25	
10322U	8	25	
10323U	10	25	




FOR RUBBER HOSE

REF.	ø INT. ø EXT.		
10331U	6/14	25	
10334U	8/14	25	
10332U	8/17	25	
10333U	10/19	25	



FOR NYLON WITH SPRING


REF.	ø INT. ø EXT.		
10341U	6x 8	25	
10342U	8x10	25	
10343U	6x10	25	
10344U	8x12	25	
10346U	10x12	25	



X 100 S


Automatic quick couplings fitted with our exclusive locking system for longer plug life. O-ring on every male thread.
 Body: nickel-plated brass
 Seals: Buna-N
 Working pressure: 0 - 12 Bar
 Working temperature: 0°C - 80°C
 Air flow at 6 Bar 1300 lt/min.
 Springs: stainless steel
 Sleeve: nylon fiberglass composite

MALE

THREAD	REF. I	REF. S	REF. USA	REF. GB	
1/4"	10501/S	10511/S	10521/S	10531/S	25
3/8"	10502/S	10512/S	10522/S	10532/S	25
1/2"	10503/S	10513/S	10523/S		25



FEMALE

THREAD	REF. I	REF. S	REF. USA	REF. GB	
1/4"	10601/S	10611/S	10621/S	10631/S	25
3/8"	10602/S	10612/S	10622/S	10632/S	25




56
57

FOR RUBBER HOSE

ø INT. ø EXT.	REF. I	REF. S	REF. USA	REF. GB	
6/14	10703/S				25
8/14	10710/S				25
8/17	10707/S				25
10/19	10709/S				25





FOR NYLON HOSE WITH SPRING

ø INT. ø EXT.	REF. I	REF. S	REF. USA	REF. GB	
6x8	10801/S	10811/S			25
8x10	10802/S	10812/S	10822/S		25
8x12	10803/S				25
					25



WITH REST

ø INT.	REF. I	REF. S	REF. USA	REF. GB	
6		10731/S	10741/S	10750/S	25
8		10733/S	10743/S	10751/S	25
9			10744/S	10752/S	25
10		10735/S	10745/S		25
13			10748/S		25



X 90

Automatic mini quick couplings for high air flow and o-ring on every male thread.

Body: nickel-plated brass

Seals: Buna-N

Working pressure: 0 - 12 Bar

Air flow at 6 Bar: 1080 lt./min.

Springs: stainless steel

Sleeve: nylon fiberglass composite

Working temperature: 0°C - 80°C

Plugs: brass

COUPLINGS

PLUGS



MALE

REF.	THREAD	Q.TY	REF.	THREAD	Q.TY
10400	1/8"	25	11400	1/8"	25
10401	1/4"	25	11401	1/4"	25



MALE



FEMALE

REF.	THREAD	Q.TY'	REF.	THREAD	Q.TY'
10410	1/8"	25	11410	1/8"	25
10411	1/4"	25	11411	1/4"	25



FEMALE



WITH REST

REF.	Ø INT.	Q.TY'	REF.	Ø INT.	Q.TY'
10420	6	25	11420	6	25
10421	8	25			



WITH REST