


9010 ECOMIX

- **Paint passage:** stainless steel
- **Needle-nozzle-springs:** stainless steel
- **Adjustments:** air-product-fan
- **Cup gasket:** o-ring in EPDM
- **Use:** application of wall paints in the building sector
- **Body:** chemically nickel plated polished aluminium
- **Cap:** chemically nickeled brass
- **Suction cup:** adjustable pressure
- **Ø nozzle:** 2,2 - 2,5 - 3,0

Equipped with regulator group of the air inlet flow and air pressure to the tank

REF.*				AIR
250**	inox 1000 cc	1470 gr	2,5 - 3 Bar	200/240 lt./min.



9010/SP ECOMIX

- **Paint passage:** stainless steel
- **Needle-nozzle-springs:** stainless steel
- **Adjustments:** air-product-fan
- **Use:** application of wall paints in the building sector
- **Body:** chemically nickel plated polished aluminium
- **Cap:** chemically nickeled brass
- **Ø nozzle:** 2,2 - 2,5 - 3,0

REF.*	SP			AIR
251**	product inlet M1/4"	610 gr.	2,5 -3 Bar	200/240 lt./min.



6
7

9011 HD

- **Paint passage:** stainless steel
- **Needle-nozzle-springs:** stainless steel
- **Adjustments:** air-product-fan
- **Pressurized gravity cup:** for high density products
- **Double air flow regulator and pressurized gravity cup with manometer**
- **Use:** for high density products like Latex, Polyurethans, Gel Coat, Thixotropic, of the wood and industrial sector
- **Body:** chemically nickel plated polished aluminium
- **Cap:** chemically nickeled brass
- **Ø nozzle:** 1,5 - 1,9 - 2,2 - 2,5

REF.*				AIR
233**	nylon 680 cc	1250 gr.	2,5 -3 Bar	220/240 lt./min
234**	aluminium 1000 cc	1260 gr.		



9010/SP COLLA

- **Paint passage:** stainless steel
- **Needle-nozzle-springs:** stainless steel
- **Adjustments:** product-fan
- **Use:** for application of fluid glues
- **Body:** chemically nickel plated polished aluminium
- **Cap:** chemically nickeled brass
- **Ø nozzle:** 1,7 -1,9

REF.*	SP			AIR
253**	product inlet M1/4"	590 gr.	2,5 -3 Bar	180/240 lt./min.



*Add nozzle Ø to the REF.

9011 GEL COAT

- **Paint passage:** stainless steel
- **Body:** chemically nickel plated polished aluminium
- **Needle-nozzle-springs:** stainless steel
- **Cap:** chemically nickeled brass
- **Adjustments:** air-product-fan
- **Ø nozzle:** 3,0 - 4,0 - 5,0
- **Use:** for application of Gel Coat and dense products generally

REF.*				
255**	nylon 680 cc	810 gr.	2,5 - 3 Bar	180/220 lt./min



9010/SP GEL COAT

- **Paint passage:** stainless steel
- **Body:** chemically nickel plated polished aluminium
- **Needle-nozzle-springs:** stainless steel
- **Cap:** chemically nickeled brass
- **Adjustments:** air-product-fan
- **Ø nozzle:** 3,0 - 4,0 - 5,0
- **Use:** chemically nickel plated polished aluminium

REF.*				
256**	product inlet M1/4"	590 gr.	2 - 3 Bar	180/240 lt./min.



*Add nozzle Ø to the REF..

G1

- **Body:** nickel-plated sanded brass
- **Needle-nozzle-springs:** stainless steel
- **Cap:** nickel-plated brass
- **Suction cup:** with adjustable pressure
- **Adjustments:** product - fan
- **Cup gasket:** o-ring in NBR
- **Equipped with regulator group of the air inlet and air pressure to the tank.**
- **Ø nozzle:** 1,9 - 2,2 - 2,5

REF.*				AIR
361**	stainless steel 1000 cc	1700 gr.	MAX 3 Bar	370 lt./min.



G1/SP

- **Body:** nickel-plated sanded brass
- **Needle-nozzle-springs:** stainless steel
- **Cap:** nickel-plated brass
- **Adjustments:** product - fan
- **Cup gasket:** o-ring in NBR
- **Ø nozzle:** 1,9 - 2,2 - 2,5

REF.*	SP			AIR
363**	product inlet M1/4"	620 gr.	MAX 3 Bar	370 lt./min.



G1/T

- **Body:** nickel-plated sanded brass
- **Needle-nozzle-springs:** stainless steel
- **Cap:** nickel-plated brass
- **Suction cup:** with adjustable pressure
- **Adjustments:** product
- **Cup gasket:** o-ring in NBR
- **Round spray**
- **Equipped with regulator group of the air inlet flow and air pressure to the tank**
- **Ø nozzle:** 1,9 - 2,2 - 2,5

REF.*				AIR
362**	stainless steel 1000 cc	1670 gr.	MAX 3 Bar	230 lt./min.



G1/T SP

- **Needle-nozzle-springs:** stainless steel
- **Cap:** nickel-plated brass
- **Adjustments:** product
- **Body:** nickel-plated sanded brass
- **Round spray**
- **Ø nozzle:** 1,9 - 2,2 - 2,5

REF.*	SP			AIR
364**	product inlet M1/4"	620 gr.	MAX 3 Bar	230 lt./min.



*Add nozzle Ø to the REF.

RD




- **Body:** nickel-plated sanded brass
- **Adjustments:** product -fan
- **Needle-nozzle-springs:** stainless steel
- **Ø nozzle:** 1,7
- **Cap:** nickel-plated brass, swivelling 360° for lateral spraying

REF.*				
36617	nylon 680 cc	1050 gr.	3 - 4 Bar	130 - 200 lt./min


NEW EPD-EPD/L

Spray gun for pressurized high density products without atomising air. Ideal for glue, sealing and lubricant.

- **Body:** nickel-plated sanded brass
- **Adjustments:** product
- **Barrel:** 100 mm with product blocking on the tip, equipped with interchangeable flat spout in metal
- **Barrel (EPD/L):** 150 mm, diam. Int. 4 mm with product blocking at the tip of the barrel on the screwable nozzle

REF.*			
36700 EPD	370 gr.	MAX 3 Bar	30/60 lt./min.
36800 EPD /L	345 gr.		


 16
17

NEW MM

- **Body:** varnished aluminium
- **Needle-springs:** brass
- **Nozzle:** nickel-plated brass
- **Use:** application of plastic wall paint
- **Cap:** nickel-plated brass
- **Adjustments:** product
- **Ø nozzle:** 4,5 - 6,0 - 8,0

REF.*				
62007	nylon 4,75 lt	1360 gr.	3,4 - 4,8 Bar	120 lt./min.



*Add nozzle Ø to the REF.